Stainless Steel Wire Rope SS 6x7-WSC

Product information



General use

Stay rope

Typical applications: Rigging, stays, controls and signalling devices. ... *Read more*

Material: AISI 316.
Marking: According to standard
Standard: EN 12385-4

Fill factor: 0.55

CERTEX Svenska AB
info@certex.se
08-758 00 10

© September 2026 - All Rights Reserved

Stainless Steel Wire Rope SS 6x7-WSC

Lifting table

Part code	Rope diameter	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Steel area mm²	Lubrication	Weight kg/100m
108100104620098	1	1,570	Stainless	sZ	0.61	0.43	No-Lube	0.38
108100154620098	1.5	1,570	Stainless	sZ	1.37	0.97	No-Lube	0.86
108100204620098	2	1,570	Stainless	sZ	2.44	1.73	No-Lube	1.54
108100254620098	2.5	1,570	Stainless	sZ	3.81	2.7	No-Lube	2.4
108100304620098	3	1,570	Stainless	sZ	5.48	3.89	No-Lube	3.46
108100404620098	4	1,570	Stainless	sZ	9.75	6.91	No-Lube	6.14
108100504620098	5	1,570	Stainless	sZ	15.2	10.8	No-Lube	9.6
108100604620098	6	1,570	Stainless	sZ	21.9	15.6	No-Lube	13.8
108100704620098	7	1,570	Stainless	sZ	29.8	21.2	No-Lube	18.8
108100804620098	8	1,570	Stainless	sZ	39	27.6	No-Lube	24.6

CERTEX Svenska AB
info@certex.se
08-758 00 10
© September 2026 - All Rights Reserved