

Steel Wire Rope POLYASS

Product information

sZ zS B G 

Rope construction: 8 strands with steel wire core.

Marking: According to standard

Standard: EN 12385-4


Note: ISO 4309 Rope Category No: 6-26mm RCN 04

Fill factor: 0.58

Winch rope



Overhead cranes



Tower crane



Part Code	Rope diameter	Steel area mm²	Min. breaking force kN 1960 N/mm²	Min. breaking force kN 1770 N/mm²	Min. breaking force kN 2160 N/mm²	Weight
101100604270110	6	16.5	25.1	-	-	15
101100654050111	6.5	19.3	29.5	26.6	-	17
101100754070111	7.5	25.7	49.2	-	-	23
101100804270111	8	29.2	49.2	-	49.2	26
101100904270111	9	37	56.5	-	-	33
101101003270111	10	45.7	69.8	-	-	41
101101103270111	11	55.3	84.4	-	-	49
101101204270111	12	65.8	100	-	-	59
101101303270111	13	77.2	118	-	-	69
101101404270111	14	89.6	137	-	-	80
101101503270111	15	103	157	-	-	92
101101603270111	16	117	179	-	-	104
101101703270111	17	132	202	-	-	118
101101803270111	18	148	226	-	-	132
101101904270111	19	165	252	-	-	147
101102004270111	20	183	279	-	-	163
101102204270111	22	221	338	-	-	197
101102403270111	24	263	402	-	-	234
101102603270111	26	309	472	-	-	275