



Wire Rope Lifting Sling WLS-175

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(* \varnothing 3mm - \varnothing 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Master link in one end and eyehook with safety latch in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

| Part code | Diameter mm | WLL ton |
|-----------|----------------|------------|
| 1603 | 3 | 0.12 |
| 1603 | 4 | 0.21 |
| 1603 | 5 | 0.32 |
| 1603 | 6 | 0.47 |
| 1603 | 7 | 0.64 |
| 1603 | 8 | 0.82 |
| 1603 | 10 | 1.28 |
| 1603 | 12 | 1.84 |

| | | |
|------|----|-------|
| 1603 | 14 | 2.51 |
| 1603 | 16 | 3.3 |
| 1603 | 18 | 4.1 |
| 1603 | 20 | 5.1 |
| 1603 | 22 | 6.2 |
| 1603 | 24 | 7.38 |
| 1603 | 26 | 8.66 |
| 1603 | 28 | 10.04 |
| 1603 | 32 | 13.12 |
| 1603 | 36 | 16.59 |
| 1603 | 40 | 20.56 |
| 1603 | 44 | 24.78 |
| 1603 | 48 | 29.55 |
| 1603 | 52 | 34.69 |

Lifting table