



Wire Rope Lifting Sling WLS-373

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²

Design: Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

| Part code | Diameter mm | WLL ton | WLL 0-45° t | WLL 45-60° t |
|-----------|-------------|---------|-------------|--------------|
| 1607 | 3 | 0.25 | 0.25 | 0.18 |
| 1607 | 4 | 0.44 | 0.44 | 0.31 |
| 1607 | 5 | 0.68 | 0.68 | 0.49 |
| 1607 | 6 | 0.98 | 0.98 | 0.7 |
| 1607 | 7 | 1.34 | 1.34 | 0.96 |
| 1607 | 8 | 1.72 | 1.72 | 1.23 |
| 1607 | 9 | 2.18 | 2.18 | 1.56 |
| 1607 | 10 | 2.69 | 2.69 | 1.92 |

| | | | | |
|------|----|-------|-------|-------|
| 1607 | 11 | 3.25 | 3.25 | 2.32 |
| 1607 | 12 | 3.85 | 3.85 | 2.75 |
| 1607 | 13 | 4.55 | 4.55 | 3.25 |
| 1607 | 14 | 5.28 | 5.28 | 3.77 |
| 1607 | 16 | 6.9 | 6.9 | 4.93 |
| 1607 | 18 | 8.71 | 8.71 | 6.22 |
| 1607 | 20 | 10.75 | 10.75 | 7.68 |
| 1607 | 22 | 13.03 | 13.03 | 9.31 |
| 1607 | 24 | 15.5 | 15.5 | 11.07 |
| 1607 | 26 | 18.19 | 18.19 | 13 |
| 1607 | 28 | 21.08 | 21.08 | 15.06 |
| 1607 | 32 | 27.56 | 27.56 | 19.69 |
| 1607 | 36 | 34.84 | 34.84 | 24.89 |
| 1607 | 40 | 43.17 | 43.17 | 30.84 |
| 1607 | 44 | 52.04 | 52.04 | 37.17 |
| 1607 | 48 | 62.06 | 62.06 | 44.33 |
| 1607 | 52 | 75.85 | 75.85 | 52.04 |

Lifting table