Wire Rope Polyamide/Nylon-coated 6x19M-WSC

Product information



General use



Slings





A galvanized rope equipped with a Wire Strand Core (WSC) and has a Transparent polyamide/nylon coating. It can be a good choice for basic lifting applications such as lifting slings, security rope in studios/theaters premises, etc.

... *Read more*

Rope construction: 6x19M-WSC
Marking: According to standard
Temperature range: App. +120°C
Finish: Polyamide/Nylon-coated
Standard: EN 12385-4
except from coating

Fill factor: 0,53

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Wire Rope Polyamide/Nylon-coated 6x19M-WSC

Lifting table

Part code	Rope diameter mm	Inner diameter mm	Colour	Tensile strength N/mm²	Min. breaking force kN	Steel area mm²	Weight kg/100m
105130500330260	5	3.3	transparent	1,770	6.98	4.55	4.8
105140500330260	5	3.3	transparent	1,960	7.73	4.55	4.8
105130600450260	6	4.5	transparent	1,770	13	8.46	8.9
105140600450260	6	4.5	transparent	1,960	14.4	8.46	8.9
105130700530260	7	5.3	transparent	1,770	18	11.7	12
105140700530260	7	5.3	transparent	1,960	19.9	11.7	12
105130800630260	8	6.3	transparent	1,770	25.4	16.6	17
105140800630260	8	6.3	transparent	1,960	28.2	16.6	17
105131000800260	10	8	transparent	1,770	41	287	29
105141000800260	10	8	transparent	1,960	45.4	16.6	29

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved