

Lifters, standard coupling Starcon

Product information

The Starcon Lifting Eye is a special steel component made for concrete casting. The sperical claw grips on to the head below the Starcon head anchor. The Starcon lifting eye has been tensile tested with 2 times of the safe load. All test results will be reported. Unique certificates are made for each delivery.

Material: Special alloy steel

Marking: According to standard, According to standard, load group, STARCON, batch code, CE

Temperature range: 200°C Finish: Electrogalvanized

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Safety factor: 4:1

| Part Code | Load grp. | L mm | A mm | B mm | C mm | D mm | Delivery time |
|--------------|-----------|---------|---------|---------|---------|---------|---------------|
| 650220013001 | 1-1.3 | 130 | 11 | 9 | 9,6 | 31 | 5 |
| 650220025001 | 1.5-2.5 | 165 | 16 | 11 | 12,4 | 35 | 5 |
| 650220050001 | 3-5.0 | 200 | 22 | 14 | 15,6 | 51,5 | 10 |
| 650220100001 | 6-10.0 | 285 | 30 | 22 | 25,5 | 69 | 10 |
| 650220200001 | 12-20.0 | 370 | 41 | 28 | 33 | 107 | 10 |

Blueprint

