Starcon Lifting Eye Flexible Coupling

Product information



The Starcon lifting eye with flexible coupling joint is used for lifting spherical anchors embedded in precast concrete elements. The spherical claw grabs the head of the spherical anchor. The mounted chain enables the Starcon lifting eye with a flexible coupling to be used at many different angles. The equipment can be reused for many lifting operations.

Areas of application: Used for Starcon spherical anchor.
Advantages: Quick connection and disconnection of anchor.
The self-locking lifting eye prevents accidental release, while the lifting eye can rotate freely around the axis of the anchor.
Its unique geometry allows the anchors to carry their full load even when pulled perpendicularly.
Ability to replace worn components.
Load group: 1.3t – 20t
Technical information: CE marking according to MD 2006/42 EF
Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

... *Read more*

Marking: CE-mark, batch code, load group + S(Starcon)
Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2.

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Starcon Lifting Eye Flexible Coupling

Blueprint



Lifting table

Part code	Load grp. t	b mm	d mm	h mm	L mm	Weight
650230013001	1-1.3	50	34	110	200	0.7
650230025001	1.5-2.5	60	42	120	233	1.28
650230050001	3-5.0	60	57	120	266	2.73
650230100001	6-10.0	100	72	200	425	7.05
650230200001	12-20.0	120	114	250	542	17

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved