

Electrical winch PRIMO

Product information



▶ Primo 500 kg CD



Electric winch for lifting and pulling of loads from 300 up to 2000 kg. A economical range of electric winches designed for simple lifting and pulling operations.

Applications:

- Leisure boat hauling
- Lifting goods
- Handling scenery
- Pulling concrete formwork on a construction site
- Lifting hatches
- Maintenance

Technical properties:

- FEM 1Cm / 1Bm – Occasional or moderate use, depending on the model.
- Drum and frame in mechanically welded, shot-blasted and painted steel.
- Greased reducer with helical gears.
- Asynchronous motor. Class F. IP 54 protection.
- Automatic lack of current brake.
- Single phase power 230V-50Hz or three phase 230/400V-50Hz depending on model.
- Electronic load limiter (from 1000 kg) and limit switch included.
- Low voltage control (BT) ensuring user protection against electrical risks.
- 3 buttons pendant control (Up - Down- Emergency Stop), not removable (3 m long control cable).

Options:

- Wire rope and hook.
- Grooved drum.
- Rope press roller.
- Tarpaulin cover.

Marking: According to standard, CE-marked

Temperature range: -10°C to +50°C

Standard: EN 13157

Part Code	WLL ton	Power	Motor kW	Weight without wire rope kg	FEM Capacity 1st layer kg	Number of layers	Speed m/min	Rope diameter mm	Max. drum capacity m	A	B	C	Ø D	E	F	Ø G	T	Total price
										mm	mm	mm	mm	mm	mm	mm	mm	
PRIMO 301 BT	0.3	1 Ph-230V	0.75	35	1Bm	360	3	9.1	48	476	422	231	89	250	214	9	257	N/A
PRIMO 303 BT	0.3	3 Ph-230/400V	0.75	35	1Bm	360	3	9.1	48	476	422	231	89	250	214	9	257	N/A
PRIMO 501 BT	0.5	1 Ph-230V	1.1	40	1Cm	630	3	11	38	476	430	241	95	250	214	9	257	N/A
PRIMO 503 BT	0.5	3 Ph-230/400V	1.1	40	1Cm	630	3	11	38	476	430	241	95	250	214	9	257	N/A
PRIMO 991 BT	0.99	1 Ph-230V	1.1	88	1Bm	1,300	4	5.2	68	565	500	326	133	260	280	17	280	N/A
PRIMO 993 BT	0.99	3 Ph-230/400V	1.1	90	1Bm	1,300	4	5.2	68	565	500	326	133	260	280	17	280	N/A

Blueprint

