



Thimble K2 - Heavy Duty Stub-end

Product information

Suitable for wire rope.

Material: Mild steel

Temperature range: -20°C up to +200°C

Finish: Galvanized

Note: Tolerance : Forged parts \pm 5%

| Part code | Rope Ø range mm | A mm | B mm | C mm | D mm | E mm | F mm | Weight kg/100pc | Delivery time |
|--------------|-----------------|-------|------|------|------|------|------|-----------------|---------------|
| 123100800360 | 8 | 50.8 | 42 | 35 | 22 | 9 | 14 | 8.2 | 5 |
| 123101000360 | 9-10 | 63.5 | 50 | 45 | 30 | 11 | 16 | 10 | 10 |
| 123101200360 | 11-12 | 76.2 | 50 | 55 | 35 | 13 | 18 | 20 | 5 |
| 123101300360 | 13 | 88.9 | 73 | 65 | 45 | 15 | 20 | 26 | 10 |
| 123101500360 | 14-15 | 101.6 | 75 | 75 | 50 | 17 | 22 | 36 | 5 |
| 123101700360 | 16-17 | 114.3 | 85 | 80 | 53 | 19 | 25 | 50 | 5 |
| 123101900360 | 18-19 | 127 | 100 | 90 | 60 | 21 | 29 | 60 | 5 |
| 123102100360 | 20-21 | 139.7 | 110 | 95 | 65 | 23 | 33 | 70 | 5 |
| 123102300360 | 22-23 | 152.4 | 115 | 120 | 70 | 25 | 34 | 100 | 5 |
| 123102700360 | 24-27 | 177.8 | 135 | 140 | 80 | 30 | 38 | 160 | 5 |
| 123103000360 | 28-30 | 203.2 | 155 | 160 | 100 | 33 | 44 | 180 | 5 |
| 123103400360 | 31-34 | 228.6 | 175 | 185 | 115 | 38 | 49 | 350 | 5 |
| 123103700360 | 35-37 | 254 | 190 | 195 | 120 | 41 | 52 | 440 | 5 |
| 123104200360 | 38-42 | 279.4 | 210 | 215 | 130 | 46 | 60 | 520 | 5 |
| 123104700360 | 43-47 | 304.8 | 245 | 250 | 145 | 52 | 65 | 730 | 10 |
| 123105400360 | 48-54 | 355.6 | 260 | 290 | 155 | 60 | 72 | 1,100 | 10 |
| 123106300360 | 55-63 | 431.8 | 310 | 370 | 190 | 70 | 84 | 1,600 | 10 |
| 123107300360 | 64-73 | 482.6 | 350 | 420 | 230 | 81 | 119 | 2,750 | 10 |
| 123108300360 | 74-83 | 558.8 | 395 | 480 | 255 | 92 | 130 | 3,650 | 10 |
| 123109500360 | 84-95 | 606.9 | 430 | 540 | 280 | 105 | 145 | 4,400 | 10 |
| 123110900360 | 96-109 | 660.4 | 450 | 580 | 285 | 120 | 155 | 4,700 | 10 |

Blueprint

