Wire Rope Dyform 8 PI

Product information



Dyform 8 PI is a high performance compacted single layer constructed rope which incorporates a plastic layer between the 8 outer strands.

- Improved bending fatigue performance
- Stable rope construction
- Diameter stability, requirement of multi-layered spooling

... *Read more*

Temperature range: -53°C up to +100°C

Fill factor: 0,68
Tolerance Ø: 0% to +5%

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Wire Rope Dyform 8 PI

Lifting table

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Lubrication	Weight
103101104270859	11	1,960	Galvanized	sZ	110	SupplierStandard	57
103101304990859	13	1,960	Galvanized	sZ	150	SupplierStandard	79
103102004990859	20	1,960	Galvanized	sZ	353	SupplierStandard	188
103104003270859	40	1,960	Galvanized	zS	1,410	SupplierStandard	74
103104004270859	40	1,960	Galvanized	sZ	1,410	SupplierStandard	754
103104206270856	42	1,960	Galvanized	zZ	1,560	C	831

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved