



## Steel Wire Rope ROPETEX S55

### Product information

**ROPETEX**



ROPETEX S55 is a rotating-resistant steel wire rope consisting of three layers of strands and a (steel) wire strand core. As the outer layer are closed in the opposite direction of the two inner layers this rope is considered as rotating-resistant steel wire rope.

Ropetex S55 is available from 9 to 20 mm and can be used for unguided single part lifting even with great lifting heights.

Ropetex S55 is good to use in several crane types like tower cranes, mobile cranes, electrical hoists and all other applications where a rotation resistant wire rope is required.

If you are searching for a comparable rope in a smaller diameter, look at Ropetex S18.

**Rope construction:** 35(W)x7

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C, for operating temperatures between 100°C and 200°C reduce MBF by minus 10 %

**Standard:** EN 12385-4

**Note:** Ropes of the class 35x7 have to be replaced always by ropes of the same/comparable class and never by ropes of class 18x7. Whereas ropes of the class 18x7 can be replaced also by ropes of 35x7 from a technical point of view.

**Fill factor:** 0,61

**RCN:** 23-2

Mobile crane



Self-erected crane



Tower crane



Luffing crane



Overhead cranes



Mobile port crane



Deck crane



Jib crane



Truck crane



<b>Part Code</b>	<b>Rope diameter mm</b>	<b>Tensile strength N/mm<sup>2</sup></b>	<b>Steel Area mm<sup>2</sup></b>	<b>Min. breaking force kN 1960 N/mm<sup>2</sup></b>	<b>Weight kg/100m</b>	<b>Total price</b>
102100904270021	9	1,960	38.9	57.2	36.8	N/A
102101004270021	10	1,960	48	70.6	45.4	N/A
102101204270021	12	1,960	69.1	102	65.4	N/A
102101304270021	13	1,960	81.1	119	76.7	N/A
102101404270021	14	1,960	94.1	138	89	N/A
102101504270021	15	1,960	108	159	102	N/A
102101604270021	16	1,960	123	181	116	N/A
102101804270021	18	1,960	156	229	147	N/A
102101904270021	19	1,960	173	255	164	N/A
102102004270021	20	1,960	192	282	182	N/A