# Marine Sling or Boat Lifting Sling

## Product information



Slings for lifting boats, the slings are white to prevent discoloration in salt water.
**Design:** Double sewn, flat woven slings with folded eyes. Alternatively with "shortening eyes" on request.
**Chemical resistance:** Resistant to most acids but not strong alkalizes.
**Stretch with working load:** 2-3%.
**Length tolerance:** Nominal length ±3%.
Always apply and use extra protections to protect the sling from sharp edges, abrasion, wear and tear, due to the shape of the boat (keel & side).
Contact CERTEX for further information.

... *Read more*

**Material:** Polyester.
**Marking:** According to standard, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instruction.
**Temperature range:** Approx. -40°C up to +100°C.
**Standard:** EN 1492-1

**Safety factor:** 7:1.

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# Marine Sling or Boat Lifting Sling

## Lifting table

| Part code | EWL m | Code | WLL ton | Webbing width mm | Colour |
|---|---|---|---|---|---|
| 341100300800030 | 8 | BSY-03080 | 3 | 90 | White |
| 341100301000030 | 10 | BSY-03100 | 3 | 90 | White |
| 341100301200030 | 12 | BSY-03120 | 3 | 90 | White |
| 341100500800030 | 8 | BSY-05080 | 5 | 150 | White |
| 341100501000030 | 10 | BSY-05100 | 5 | 150 | White |
| 341100501200030 | 12 | BSY-05120 | 5 | 150 | White |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved