

Marine Slings or Boat Lifting Slings

Product information



Slings for lifting boats, the slings are white to prevent discoloration in salt water.

Design: Double sewn, flat woven slings with folded eyes. Alternatively with "shortening eyes" on request.

Chemical resistance: Resistant to most acids but not strong alkalizes.

Stretch with working load: 2-3%.

Length tolerance: Nominal length $\pm 3\%$.

Always apply and use extra protections to protect the sling from sharp edges, abrasion, wear and tear, due to the shape of the boat (keel & side).

Contact CERTEX for further information.

[... Read more](#)

Material: Polyester.

Marking: According to standard, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instruction.

Temperature range: Approx. -40°C up to $+100^{\circ}\text{C}$.

Standard: EN 1492-1

Safety factor: 7:1.

Marine Sling or Boat Lifting Sling

Lifting table

Part code	EWL m	Code	WLL ton	Webbing width mm	Colour
341100300800030	8	BSY-03080	3	90	White
341100301000030	10	BSY-03100	3	90	White
341100301200030	12	BSY-03120	3	90	White
341100500800030	8	BSY-05080	5	150	White
341100501000030	10	BSY-05100	5	150	White
341100501200030	12	BSY-05120	5	150	White