

Webbing Sling Secutex

Product information

General: For all types of lifting within industry. Extremely good cutting resistance and high wear strength.

Design: Flat woven, colour coded slings with folded soft eyes.

Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL) $\pm 3\%$.

... [Read more](#)



Material: Polyester with 5 mm polyurethane cover. Resistant to most acids but not strong alkalizes.

Marking: According to standard, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instruction.

Temperature range: app. -30° - $+70^{\circ}\text{C}$, short expose to apx $+90^{\circ}\text{C}$.

Standard: EN 1492-1

Safety factor: 7:1.

Webbing Sling Secutex

Blueprint



Lifting table

| Part code | WLL ton | Webbing width mm | Colour |
|-----------------|---------|------------------|--------|
| 34110010XXX0040 | 1 | 30 | Violet |
| 34110020XXX0040 | 2 | 60 | Green |
| 34110030XXX0040 | 3 | 90 | Yellow |
| 34110040XXX0040 | 4 | 120 | Grey |
| 34110050XXX0040 | 5 | 150 | Red |
| 34110080XXX0040 | 8 | 240 | Blue |