
Webbing Sling Secutex

Product information

General: For all types of lifting within industry. Extreamly good cutting resistance and high wear strength.
Design: Flat woven, colour coded slings with folded soft eyes.



Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL) ±3%.

... *Read more*

Material: Polyester with 5 mm polyurethane cover. Resistant to most acids but not strong alkalizes.
Marking: According to standard, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instruction.
Temperature range: app. -30° - +70°C, short expose to apx +90°C.
Standard: EN 1492-1


Safety factor: 7:1.

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Webbing Sling Secutex

Blueprint



Lifting table

Part code	WLL ton	Webbing width mm	Colour
34110010XXX0040	1	30	Violet
34110020XXX0040	2	60	Green
34110030XXX0040	3	90	Yellow
34110040XXX0040	4	120	Grey
34110050XXX0040	5	150	Red
34110080XXX0040	8	240	Blue

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved