Webbing Sling Secutex/C-hook

Product information

General: For all types of lifting within industry. Extreamly good cutting resistance and high wear strength.
Design: Flat woven, colour coded slings with folded soft eye in one end and a C-hook in the other end. One side coated with polyurethane, double side coated on request.



Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL) ±3%.

... *Read more*


Material: Polyester with 5 mm polyurethane cover. Resistant to most acids but not strong alkalizes.
Marking: According to standard, The slings are provided with a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instruction.
Temperature range: app. -30° - +70°C, short expose to apx +90°C.
Standard: EN 1492-1

Safety factor: 7:1.

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

Webbing Sling Secutex/C-hook

Blueprint



Lifting table

Part code	WLL ton	Webbing width mm	Colour
34110010XXX0050	1	30	Violet
34110020XXX0050	2	60	Green
34110030XXX0050	3	90	Yellow
34110040XXX0050	4	150	Red

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved