Lever Hoist Lincoln Hoist

Product information



Lincoln Hoist™ is a high-quality and durable solution for demanding lifting and pulling use. It is ideal for forestry applications, but can also be used for direct lifting. All the components are manufactured in the USA, guaranteeing high quality and reliability.

By using the wire rope as a double, the lifting capacity can be doubled.

Features and benefits:

- Load tested to 125% of rated capacity.
- Handle bends to alert operator of overload.
- Interlocking pawl mechanism - no brakes to slip.
- Quick release allows cable to be pulled out freely when rigging.
- Maintenance free bearings are lubed for life.
- Reversible handle allows pulling in optimum position.
- Open frame construction for easy inspection and cleaning.
- Four hook styles designed to meet application requirements and work practice standards.
- Swivel hooks are drop forged, heat treated steel.
- Hydraulically crimped copper sleeve for uniform hold.
- All cable stores on drum.

The Lincoln Hoist™ is the professional's reliable choice, combining lightweight, durability and ease of use in demanding conditions.

... *Read more*

Marking: CE-mark, Rate badge.
Note: Spare parts also available

Safety factor: 4:1.

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lever Hoist Lincoln Hoist

Lifting table

Part code	Code	WLL ton	Lifting height m	Rope Ø mm	WLL double ton	Min hook to hook Single mm	Min hook to hook Double mm	Lifting height double m	Weight kg
501100050300040	LH 3000-10-CE	0.5	3	5.55	1	508	584	1.5	4.1
501100050910040	LH 3000-30-CE	0.5	9.14	5.55	1	559	559	4.6	6.24
501100060610040	LH 4000-20-CE	0.55	6.1	6.35	1.1	559	737	3	7

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved