Wire Rope Clamp BG

Product information



General: Wire rope clamp type, approved for lifting. Requires fewer clamps per fixation, e.g. two wire clamps instead of four, for 16 mm cable. Symmetrical – cannot be wrongly fitted. The clamps ensure fixation of the wire to a degree of at least 90% of the minimum breaking load of the wire in accordance with the current European standard.

Design: Bases of cast steel.

... *Read more*

Finish: Body Hot dip galvanized and bolt electro galvanized
Note: Follow the fitting instructions in the user manual before use. Not for use with compacted or hammered wire ropes.

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Wire Rope Clamp BG

Lifting table

Part code	Rope Ø range mm	Thread	No. of clips when lifting	Torque Nm	Weight kg/100pc
121100600050	5-6	M6	2	9,5	9
121100800050	6.5-8	M6	2	9,5	12
121101000050	8.5-10	M8	2	22	20
121101250050	11-12.5	M10	2	44	39
121101600050	13-16	M12	2	75	72
121102000050	17-20	M14	2	120	120
121102500050	21-25	M18	2	260	280
121103400050	26-34	M20	2	350	770

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved