



## Snatch Block with Eye

### Product information

Intended for general lifting purposes and on board ships. Provided with swivelling oval eye. SWL refers to working load limit (WLL) of the wire rope. (The concept SWL is only used on ships).

**Design:** Covering side plates with separate steel supports (except 400-E). Key hole type locking. Bronze bushed sheaves of steel, except 125-E which has a polyamid PA 6G sheave. Countersunk grease fitting in the shaft. The oval eye is swivelling and jointed attached to the cross head.

**Material:** Structural steel, forged oval eyes and cross head of steel, sheave bushing of red metal.

**Marking:** Type, WLL and max wire rope diameter.

**Finish:** Grey painted, 400-E is blue painted.

**Note:** The blocks can be manufactured with a hook instead of an eye. We also manufacture loadblocks, guide pullies and pendant rope blocks and multiple sheave blocks.

Part code	Rope Ø range	WLL ton	a mm	b mm mm	D, mm	E mm	g mm mm	K mm	L mm	Weight kg	Delivery time
424100100070	9	1	60	34	125	105	18	110	210	3.5	10
424100200070	11	2	58	26	150	125	18	115	235	6	10
424100300070	15	3	72	32	200	170	23	155	325	12	10
424100500070	18	5	94	40	250	210	28	190	390	20.5	10
424101000070	26	10	125	54	350	300	39	270	475	47	10
424101250070	30	12.5	170	75	406	342	55	215	720	113	10

# Blueprint

