Cablegrip LE Single Eye

Product information

General: A robust sock to pull any wire rope and wire in pure aluminum or copper. Has extra long braid in secitions of triple-double and single wire. The model has a soft eye to fit a swivel. To counteract attrition, and increase the life time the sock is fitted with aluminum collars.
Design: Intertwined - triple, double and single.

... *Read more*



Material: : Steel wire - galvanized.
Warning: Margin of safety is applied to all specified breaking loads. Additional safety factors, depending on area of use should be applied. CERTEX recommends a safety factor of 3:1 for horizontal pulls and 5:1 for overhead pulling. The breaking load varies with the material, shape, and also the diameter of the product.

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

Cablegrip LE Single Eye

Blueprint



Lifting table

Part code	Diameter mm	Rope Ø range mm	MBL ton	Length Net	Eye length mm	Weight kg
140601200210	6	6.5-12	1.63	660	185	0.24
140601900210	8	13-19	3.17	815	225	0.52
140602500210	8	19-25	4.54	1,045	225	0.7
140603800210	12	32-38	10.72	1,425	370	2.06
140605700210	14	44.5-57	16.92	1,785	430	3.6

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved