

## Cablegrip DE Single Eye

### Product information



**General:** Primarily intended for wiring, but can also be used with steel wire and piping. Default is soft eye but is available with thimble.

**Rope construction:** : Braided double ropes.

**Material:** : Steel wire - Galvanized.

**Warning:** Margin of safety is applied to all specified breaking loads. Additional safety factors, depending on area of use should be applied. CERTEX recommends a safety factor of 3:1 for horizontal pulls and 5:1 for overhead pulling. The breaking load varies with the material, shape, and also the diameter of the product.

Part Code	Diameter mm	Rope diameter mm	MBL ton	Breaking load ton	Length Eye	Length Net	Weight kg	Total price
10.42DE000812S	5	8-12.5	-	0,88	120	400	0.15	N/A
10.42DE001215S	5	12.5-15.5	1.41	-	125	550	0.22	N/A
10.42DE001519S	6	15.5-19	1.76	-	155	600	0.29	N/A
10.42DE001925S	6	19-25	2.11	-	175	600	0.32	N/A
10.42DE002538S	6	25-38	3.03	-	200	600	0.41	N/A
10.42DE003850S	8	38-50.5	4.39	-	260	600	0.66	N/A
10.42DE005063S	8	50.5-63.5	5.41	-	285	600	0.76	N/A
10.42DE006376S	9	63.5-76	7.22	-	330	600	1.06	N/A
10.42DE007689S	9	76-89	7.22	-	345	650	1.12	N/A
10.42DE089101S	10	89-101.5	9.03	-	370	650	1.43	N/A

## Blueprint

E - Einzel Ögeln

