Cablegrip ASK

Product information

General: Openi sock with a pressed-in eye for wire rope and and cable drawing or tubing fuse. The sock can be placed anywhere along the cable, rope or hose and then "snapped together". The eyes can be ordered with a thimble.

... *Read more*



Rope construction: : Braided double ropes.
Material: : Steel wire - galvanized.
Warning: Margin of safety is applied to all specified breaking loads. Additional safety factors, depending on area of use should be applied. CERTEX recommends a safety factor of 3:1 for horizontal pulls and 5:1 for overhead pulling. The breaking load varies with the material, shape, and also the diameter of the product.

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

Cablegrip ASK

Blueprint



Lifting table

Part code	Diameter mm	Rope Ø range mm	MBL ton	Length Net	Eye length mm	Weight kg
140601500260	4	12-15	0.35	155	250	0.08
140601900260	4	15.5-19	0.435	155	250	0.08
140602500260	5	19-25	0.615	170	300	0.14
140603800260	6	25-38	1.17	170	300	0.25
140605000260	6	38-50	1.68	230	350	0.31

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved