# Lifting Point POWERTEX LPD - Long Bolt version

**Product information**



The Powertex LPD lifting point with a decentered link and long bolt is a 360° rotating and 150° pivoting lifting point for industrial lifting applications. The extra-long bolt and nut make this version suitable for mounting through holes. Its spacious forged D-shaped link and uniform WLL in all permitted loading directions support flexible load connection and simpler load planning.

**Best used for**

- Through-hole mounting where an extra-long bolt and nut are required
- Lifting applications requiring the same WLL in different loading directions.
- Vibrating machinery and vehicles where reduced rattling is beneficial.

**Not ideal for**

- Rotation under load. Use a ball-bearing lifting point such as POWERTEX LPB instead.

**Product benefits**

- Extra-long bolt and nut enable mounting through holes.
- 360° rotation and 150° pivot motion accommodate changing load directions.
- Uniform WLL in all directions simplifies load planning.
- Integrated spring reduces rattling and holds the D-ring vertically.
- Tested in accordance with EN 1677-1 and AS 3776 requirements.
- Each lifting point is crack-detection tested, and production samples are proof-load tested. The product design is fatigue-tested to 20,000 cycles at 1.5 times the WLL.
- The traceability code links components to the production lot and raw materials.
- Full WLL from -40°C to +200°C, with reductions at higher temperatures

... Read more

**Features:** 360 degrees rotatable, quiet, spacious link, through hole mounting
**Material:** Forged alloy steel
**Marking:** According to standard, CE-mark, UKCA-marked, POWERTEX, model name, WLL and batch number
**Temperature range:** -40 up to +200°C without reduction in WLL
**Finish:** Powder painted in PURE RED
**Standard:** EN 1677-1, AS 3776
**Note:** Before use, review the WLL diagram to select the correct LPD for your application


**Safety factor:** 4:1

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# Lifting Point POWERTEX LPD - Long Bolt version

## Blueprint



## Lifting table

| Part code | WLL ton | Thread mm | Model | Torque Nm | E mm | A mm | B mm | C mm | D mm | F mm | G mm | N mm | L mm | S mm | SW mm | M mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4215LPDM8LB | 0.3 | M8 | LPD-M8LB | 30 | 64 | 34 | 37 | 42 | 14 | 98.5 | 57 | 31 | 42.5 | 6 | 13 | M8 | 0.5 |
| 4215LPDM10LB | 0.63 | M10 | LPD-M10LB | 60 | 80 | 34 | 37 | 44 | 14 | 98.5 | 57 | 31 | 40.5 | 6 | 16 | M10 | 0.5 |
| 4215LPDM12LB | 1 | M12 | LPD-M12LB | 100 | 104 | 34 | 37 | 45 | 14 | 98.5 | 57 | 31 | 39.5 | 8 | 18 | M12 | 0.6 |
| 4215LPDM16LB | 1.5 | M16 | LPD-M16LB | 150 | 128 | 34 | 37 | 48 | 14 | 98.5 | 57 | 31 | 36.5 | 10 | 24 | M16 | 0.7 |
| 4215LPDM20LB | 2.5 | M20 | LPD-M20LB | 250 | 160 | 50 | 54 | 58 | 16.5 | 143 | 82 | 45 | 68.5 | 12 | 30 | M20 | 1.7 |
| 4215LPDM24LB | 4 | M24 | LPD-M24LB | 400 | 192 | 50 | 54 | 61 | 16.5 | 143 | 82 | 45 | 65.5 | 14 | 36 | M24 | 2 |
| 4215LPDM30LB | 5 | M30 | LPD-M30LB | 500 | 240 | 60 | 65 | 82 | 22 | 170 | 99 | 59 | 66 | 17 | 46 | M30 | 4.1 |
| 4215LPDM36LB | 8 | M36 | LPD-M36LB | 800 | 288 | 77 | 85 | 104 | 27 | 226.5 | 123 | 69 | 95.5 | 22 | 55 | M36 | 7.6 |
| 4215LPDM42LB | 15 | M42 | LPD-M42LB | 1,500 | 336 | 95 | 104 | 117 | 36 | 257.5 | 158 | 98 | 104.5 | 22 | 65 | M42 | 14 |
| 4215LPDM48LB | 20 | M48 | LPD-M48LB | 2,000 | 384 | 95 | 104 | 120 | 36 | 257.5 | 158 | 98 | 101.5 | 27 | 75 | M48 | 16 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved