



## Ferrule INOX Talurit®

### Product information



These ferrules are normally used on stainless steel wire ropes to achieve the best possible resistance against corrosion.

Stainless steel Ferrule - recommended for machine pressing only. Suitable for long term use in salt water, waste water treatment and chemical processing.

**Material:** Stainless steel, AISI 316.

**Note:** See the manufacturer's product data sheet below for guidance on dimension selection. We do not guarantee strength of slings for lifting activities made of INOX ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of the minimum-breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

Part code	Ferrule size mm mm	Delivery time
120100100110	1	5
120100150110	1.5	10
120100200110	2	5
120100250110	2.5	5
120100300110	3	5
120100350110	3.5	5
120100400110	4	5

120100450110	4.5	5
120100500110	5	5
120100600110	6	5
120100700110	7	5
120100800110	8	5
120100900110	9	5
120101000110	10	5
120101100110	11	5
120101200110	12	5
120101300110	13	10
120101400110	14	5
120101600110	16	5
120101800110	18	5
120102000110	20	10
120102200110	22	10
120102400110	24	10
120102700110	26	10
120102800110	28	10
120103000110	30	10
120103200110	32	10