# Ferrule INOX Talurit®

**Product information**



These ferrules are normally used on stainless steel wire ropes to achieve the best possible resistance against corrosion.

Stainless steel Ferrule - recommended for machine pressing only. Suitable for long term use in salt water, waste water treatment and chemical processing

... *Read more*

**Material:** Stainless steel, AISI 316.
**Note:** See the manufacturer's product data sheet below for guidance on dimension selection. We do not guarantee strength of slings for lifting activities made of INOX ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of the minimum-breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# Ferrule INOX Talurit®

## Lifting table

| Part code | Ferrule size mm |
|---|---|
| 120100100110 | 1 |
| 120100150110 | 1.5 |
| 120100200110 | 2 |
| 120100250110 | 2.5 |
| 120100300110 | 3 |
| 120100350110 | 3.5 |
| 120100400110 | 4 |
| 120100450110 | 4.5 |
| 120100500110 | 5 |
| 120100600110 | 6 |
| 120100700110 | 7 |
| 120100800110 | 8 |
| 120100900110 | 9 |
| 120101000110 | 10 |
| 120101100110 | 11 |
| 120101200110 | 12 |
| 120101300110 | 13 |
| 120101400110 | 14 |
| 120101600110 | 16 |
| 120101800110 | 18 |
| 120102000110 | 20 |
| 120102200110 | 22 |
| 120102400110 | 24 |
| 120102700110 | 26 |
| 120102800110 | 28 |
| 120103000110 | 30 |
| 120103200110 | 32 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved