

Ferrule TKH Talurit®



Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

Conical ferrule with an inspection hole to ensure the short end of the wire rope is correctly positioned after swaging. This hole remains open after swaging, due to the pressing in a die with a blind tap.

The ferrules can be used for fibre core, single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and some spiral strand ropes.

Material: Aluminium

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Part code	Ferrule size mm mm	Delivery time
120100800200	8	5
120100900200	9	5
120101000200	10	5
120101100200	11	5
120101200200	12	5
120101300200	13	5
120101400200	14	5

120101600200	16	5
120101800200	18	5
120102000200	20	5
120102200200	22	5
120102400200	24	5
120102600200	26	10
120102800200	28	5
120103000200	30	10
120103200200	32	10
120103400200	34	5
120103600200	36	5
120103800200	38	5
120104000200	40	10
120104400200	44	10
120105000200	50	10
120105400200	54	10
120104200200	42	10
120104600200	46	10
120100700200	7	10
120100650200	6.5	10
120104800200	48	10
120105200200	52	10
120105600200	56	10

120105800200

58

10

120106000200

60

10