Black Belt Sling™ Extreema® with HMPE core

Product information



These Extreema® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt Sling™ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of general HMPE (Trosar®), which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordura® outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

When to choose this product

Best for:

- Heavy lifting with cranes, shackles, and large connection points
- Environments with high abrasion and repeated handling

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- Floats on water
- Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m – 65m
- Standard with RFID

... *Read more*

Material: PES, Dyneema
Marking: CE-mark
Temperature range: -40°C up to +70°C

Safety factor: 7:1

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Black Belt Sling™ Extreema® with HMPE core

Lifting table

Part code	Code	WLL ton
34050200XXX0140	EXHCO/20/XXX	20
34050250XXX0140	EXHCO/25/XXX	25
34050300XXX0140	EXHCO/30/XXX	30
34050400XXX0140	EXHCO/40/XXX	40
34050500XXX0140	EXHCO/50/XXX	50
34050700XXX0140	EXHCO/70/XXX	70
34050750XXX0140	EXHCO/75/XXX	75
34051000XXX0140	EXHCO/100/XXX	100
34051200XXX0140	EXHCO/120/XXX	120
34051250XXX0140	EXHCO/125/XXX	125
34051500XXX0140	EXHCO/150/XXX	150
34052000XXX0140	EXHCO/200/XXX	200

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved