

Coil Hook Type CKBM



Product information



Counterbalanced

General: For small or medium-sized loads and moderate coil widths. See the introductory text above in the section on C-hooks.

Design: Hollow beam that is lighter in weight than equivalent steel plate. The counterbalance ensures that the fork is always in a horizontal position, regardless of whether the hook is empty or loaded.

Proof: 1,5 x WLL.

Material: Hollow-beam of high-strength structural steel.

Marking: Type, working load limit, maximum coil width and CE marking.

Finish: Yellow painted.

Note: We recommend the use of a 2-leg chain sling, headroom permitting as an increase in dimension L provides better balance.

Safety factor: 1,5 x WLL.

| Part Code | WLL ton | Max coil width mm | B mm | C mm | E mm | G mm | H mm | L mm | S mm | Weight kg | Delivery time |
|-----------------|---------|-------------------|------|------|------|------|------|------|------|-----------|---------------|
| 503500153800050 | 1.5 | 380 | 50 | 100 | 300 | 100 | 500 | 300 | 110 | 25 | 10 |
| 503500205000050 | 2 | 500 | 50 | 100 | 375 | 60 | 500 | 310 | 120 | 80 | 10 |
| 503500358500050 | 3.5 | 850 | 75 | 150 | 600 | 100 | 500 | 420 | 150 | 130 | 10 |
| 503500758500050 | 7.5 | 850 | 90 | 200 | 750 | 100 | 550 | 500 | 200 | 240 | 10 |

Blueprint

