

Crane End Stop ES

Product information



End stops for crane rope applications.

Features: These end stops are designed for full load applications of rotation resistant and low rotation ropes. The chamfered surface around the cylinder matches different fitting devices. The bore of the end stop is slightly conical to distribute the stress over a larger area.

The exact diameter and length of the end stop assembly should be confirmed when an order is placed to ensure a good match between stop and device.

The end stop is specifically manufactured for rotation resistant and low rotational ropes with a fill factor between 0.61 and 0.76. For other rope types please contact us.

[... Read more](#)

Material: Mild carbon steel.

Marking: ID code and Manufacturer's symbol.

Temperature range: -40°C to 150°C.

Finish: Ungalvanised.

Crane End Stop ES

Lifting table

| Part code | Code | Rope Ø range mm | Finish length mm |
|-------------|---------|--------------------|---------------------|
| 1205ES13D30 | ES13D30 | 13 | 90 |
| 1205ES14D30 | ES14D30 | 14 | 90 |
| 1205ES15D30 | ES15D30 | 15 | 90 |
| 1205ES16D36 | ES16D36 | 16 | 108 |
| 1205ES17D36 | ES17D36 | 17 | 108 |
| 1205ES18D36 | ES18D36 | 18 | 108 |
| 1205ES19D44 | ES19D44 | 19 | 126 |
| 1205ES20D44 | ES20D44 | 20 | 126 |
| 1205ES21D44 | ES21D44 | 21 | 126 |
| 1205ES22D44 | ES22D44 | 22 | 126 |
| 1205ES23D52 | ES23D52 | 23 | 144 |
| 1205ES24D52 | ES24D52 | 24 | 144 |
| 1205ES25D52 | ES25D52 | 25 | 144 |
| 1205ES26D52 | ES26D52 | 26 | 144 |
| 1205ES26D58 | ES26D58 | 26 | 161 |
| 1205ES27D58 | ES27D58 | 27 | 174 |
| 1205ES28D58 | ES28D58 | 28 | 174 |
| 1205ES29D58 | ES29D58 | 29 | 174 |
| 1205ES30D64 | ES30D64 | 30 | 192 |
| 1205ES31D64 | ES31D64 | 31 | 192 |
| 1205ES32D64 | ES32D64 | 32 | 192 |