

Powertex Chain Sling G10 in Box PCSB-A-026

Product information



POWERTEX

Our smart chain sling system in Grade 10 consists of 1-leg and 2-leg slings that can be used directly from the box.

The smart slings can instantly be combined on the crane hook to lift loads that require 3 or 4 legs to be used.

Features:

- Multifunctional chain slings Grade 10 packed in box having all necessary markings and documents and ready for use
- The smart stainless steel sling tag gives information of the WLL for the sling as configured, but also when used in any 1-4 leg PCSB combination
- Two 1-leg or 2-leg PCSB slings can easy and safely be combined on the crane hook to perform 2-leg, 3-leg and 4-leg lifting operation thanks to the smart sling tag
- 2-leg slings can also safely be used in a 1-leg lifting operation as adequate information is given on the smart sling tag (Non-used leg should be hooked to the master link to avoid snagging)
- +25% higher lifting capacity (WLL) compared to standard Grade 8 slings
- Light weight thanks to the smart, multifunctional top components
- Cost effective compared to conventional slings thanks to use of multifunctional components
- Shortening function is integrated in the master link connector allowing the chain legs to be adjusted instantly
- Shortening can be made from either side of the shortener which is a safety advantage compared to shortening clutch.
- No reduction of WLL when shortening the chains thanks to the well. ... [Read more](#)

Material: Quenched and Tempered Alloy Steel of Grade 10 quality

Marking: According to standard, CE-marked, WLL, Chain size, Length, Grade 10, Serial number, MFG date, QR code leading to user manual

Temperature range: -40°C up to +200°C without reduction of WLL

Finish: Painted blue

Standard: EN 818-4

(+ 25% WLL) and ASTM A973

Safety factor: 4:1

Grade: 10

Powertex Chain Sling G10 in Box PCSB-A-026

Lifting table

| Part code | EWL m | Chain diameter mm | WLL ton | Description | Number of legs | Weight kg |
|-----------------|----------|----------------------|------------|--|----------------|--------------|
| 240500600300010 | 3 | 6 | 1.4 | Grab Masterlink X-A04 and Clevis Self Locking hook X-026 | 1 | 3.6 |
| 240500600500010 | 5 | 6 | 1.4 | Grab Masterlink X-A04 and Clevis Self Locking hook X-026 | 1 | 5.4 |
| 240800600300010 | 3 | 6 | 2 | Grab Masterlink X-A05 and Clevis Self Locking hooks X-026 | 2 | 6.7 |
| 240800600500010 | 5 | 6 | 2 | Grab Masterlink X-A05 and Clevis Self Locking hooks X-026 | 2 | 10.3 |
| 240500800300010 | 3 | 8 | 2.5 | Grab Masterlink X-A04 and Clevis Self Locking hook X-026 | 1 | 6.4 |
| 240500800500010 | 5 | 8 | 2.5 | Grab Masterlink X-A04 and Clevis Self Locking hook X-026 | 1 | 9.6 |
| 240800800300010 | 3 | 8 | 3.55 | Grab Masterlink X-A05 and Clevis Self Locking hooks X-026 | 2 | 11.5 |
| 240800800500010 | 5 | 8 | 3.55 | Grab Masterlink X-A05 and Clevis Self Locking hooks X-026 | 2 | 17.9 |
| 240501000300010 | 3 | 10 | 4 | Grab Masterlink X-A04 and Clevis Self Locking hook X-026 | 1 | 10.1 |
| 240501000600010 | 6 | 10 | 4 | Grab Masterlink X-A04 and Clevis Self Locking hook X-026 | 1 | 17.6 |
| 240801000300010 | 3 | 10 | 5.6 | Grab Masterlink X-A05 and Clevis Self Locking hooks X-026 | 2 | 18.1 |
| 240801000600010 | 6 | 10 | 5.6 | Grab Masterlink X-A05 and Clevis Self Locking hooks X-026 | 2 | 33.1 |
| 240501300300010 | 3 | 13 | 6.7 | Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026 | 1 | 18.8 |
| 240501300600010 | 6 | 13 | 6.7 | Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026 | 1 | 31.7 |
| 240801300300010 | 3 | 13 | 9.5 | Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026 | 2 | 34.5 |
| 240801300600010 | 6 | 13 | 9.5 | Extra large Grab Masterlink X-001-251+X-079-13 and Self Locking hook X-026 | 2 | 60.3 |