Stainless Steel Swage Studs with Metric threads

Product information



Product features

- Approved suitable for lifting.
- Available for stainless steel wire rope diameters from 3 mm up to 26 mm.
- Also available with UNF threads.
- Other sizes, custom lengths or threads on request.

Quality features

- Validated for construction 6x19-WSC and 6x36-IWRC in grade 1570 N/mm^2
- Terminal efficiency of 90% in accordance with EN 13411-8
- Fatigue rated in accordance with EN 13411-8
- Material and conformity certificates available on request

Typical applications

General lifting, including for off-shore applications. General lifting and tethering in leisure marine applications - not submerged.

... *Read more*


Material: Manufactured from 316L stainless steel
Marking: According to standard
Standard: EN 13411-8

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Stainless Steel Swage Studs with Metric threads

Blueprint



Lifting table

Part code	Rope Ø range mm	Type	B mm	D mm	L mm	CT mm	TH mm mm	A/F mm
1207SCM6X3REN	3	Right	39	6,3	97	47	M6	5
1207SCM6X4REN	4	Right	45	7,5	105	47	M6	6
1207SCM8X4REN	4	Right	45	7,5	113	54	M8	6
1207SCM8X5REN	5	Right	52	9,1	122	54	M8	8
1207SCM10X5REN	5	Right	52	9,1	135	64	M10	8
1207SCM10X6REN	6	Right	65	12,5	154	75	M10	11
1207SCM12X6REN	6	Right	65	12,5	170	90	M12	11
1207SCM12X7REN	7	Right	70	14,3	177	90	M12	12
1207SCM12X8REN	8	Right	80	16	190	90	M12	14
1207SCM16X8REN	8	Right	80	16	201	100	M16	14
1207SCM16X10REN	10	Right	100	18	223	100	M16	16
1207SCM20X12REN	12	Right	132	21,4	277	120	M20	19
1207SCM20X12LEN	12	Left	132	21.4	277	120	M20	19
1207SCM22X14REN	14	Right	156	25	325	140	M22	22
1207SCM27X16REN	16	Right	176	28,2	371	160	M27	25

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved