

## Lever Hoist POWERTEX PLH-S2OLP



### Product information

**POWERTEX**



POWERTEX PLH-S2OLP Lever Hoist is a hoist of high quality which is durable and easy to operate using the ergonomic ratchet lever. The OLP hoists are factory equipped with Overload Protection device, which limits the maximum operating force that can be applied using the ratchet handle.

#### Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- Fine calibrated European made COROLIM® protected load chain for smooth operation
- The unique surface treatment gives excellent corrosion protection and quiet run
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

**Material:** Durable all steel construction

**Marking:** According to standard, CE-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

**Temperature range:** -10°C up to +50°C

**Finish:** Powder coated finish and plated frame components


**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1


Part Code	WLL ton	Lifting height m	Model	Load chain mm	Number of falls	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H min mm	Weight kg	Delivery time
500500050150471	0.5	1.5	PLH-S2OLP/500KG	5,0 x 15,0	1	24.8	150	90	118	253	22	32	310	5.2	10
500500050300471	0.5	3	PLH-S2OLP/500KG	5,0 x 15,0	1	24.8	150	90	118	253	22	32	310	6	10
500500080150471	0.8	1.5	PLH-S2OLP/800KG	5,6 x 17,0	1	26.5	158	98	132	273	26	36	340	6.6	10
500500080300471	0.8	3	PLH-S2OLP/800KG	5,6 x 17,0	1	26.5	158	98	132	273	26	36	340	7.6	10
500500160150471	1.6	1.5	PLH-S2OLP/1600KG	7,1 x 21,0	1	29.5	185	111	145	378	29	43	400	11	10
500500160300471	1.6	3	PLH-S2OLP/1600KG	7,1 x 21,0	1	29.5	185	111	145	378	29	43	400	12.6	10
500500320150471	3.2	1.5	PLH-S2OLP/3200KG	10,0 x 28,0	1	33.5	212	124	198	418	37	50	520	19.9	10
500500320300471	3.2	3	PLH-S2OLP/3200KG	10,0 x 28,0	1	33.5	212	124	198	418	37	50	520	23.2	10
500500630150471	6.3	1.5	PLH-S2OLP/6300KG	10,0 x 28,0	2	37	212	124	230	418	43	53	640	24.6	10
500500630300471	6.3	3	PLH-S2OLP/6300KG	10,0 x 28,0	2	37	212	124	230	418	43	53	640	31.2	10
500500900150471	9	1.5	PLH-S2OLP/9000KG	10,0 x 28,0	3	42	212	124	338	418	44	67	730	50	10
500500900300471	9	3	PLH-S2OLP/9000KG	10,0 x 28,0	3	42	212	124	338	418	44	67	730	60	10

# Blueprint

0,25 t - 3,2 t



6,3 t



9,0 t

