

Female Swivel eye bolt Codipro FE SEB UP

Product information



The SEB lifting eye nut is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load.
- Safe alternative to C15 DIN 580 eye nuts.
- Torque key adaptor available on request.

[... Read more](#)

Material: High tensile steel

Marking: According to standard, CE-marked


Temperature range: -20°C up to +200°C

Standard: EN 1677-1
except grade/WLL

Safety factor: 5:1

Female Swivel eye bolt Codipro FE SEB UP

Blueprint



Lifting table

| Part code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | L max. mm | Weight kg |
|----------------|---------|--------------|-----------|------|------|------|------|-----------|-----------|
| 4215FESEBM8UP | 0.4 | M 8 (x1,25) | 6 | 38 | 45 | 88 | 80 | 22 | 0.8 |
| 4215FESEBM10UP | 0.5 | M 10 (x1,50) | 10 | 38 | 45 | 88 | 80 | 22 | 0.8 |
| 4215FESEBM12UP | 0.8 | M 12 (x1,75) | 15 | 38 | 45 | 88 | 80 | 22 | 0.8 |
| 4215FESEBM16UP | 1.4 | M 16 (x2) | 50 | 38 | 45 | 88 | 80 | 22 | 0.8 |
| 4215FESEBM20UP | 2 | M 20 (x2,5) | 100 | 55 | 70 | 115 | 106 | 35 | 2.5 |
| 4215FESEBM24UP | 3.4 | M 24 (x3) | 160 | 77 | 94 | 168 | 155 | 48 | 6.3 |
| 4215FESEBM30UP | 5.5 | M 30 (x3,5) | 250 | 77 | 94 | 168 | 155 | 48 | 6.3 |
| 4215FESEBM36UP | 9 | M 36 (x4) | 320 | 77 | 94 | 168 | 155 | 48 | 6.3 |