

Swivel Eye Bolt Codipro SEB UP

Product information



The SEB lifting ring is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load
- Safe alternative to C15 DIN 580 eye bolts.
- Torque key adaptor available on request.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Standard: EN 1677-1

except grade/WLL

Note: On request the product can be certified for lashing.

Safety factor: 5:1

Part Code	WLL ton	Thread	Torque Nm	StandardL1 mm	X/X mm	S mm	A mm	B mm	C mm	D mm	Weight kg	Delivery time
4215SEBM8UP	0.4	M 8 (x1.25)	6	14	20	6	30	34	60	57	0.24	10
4215SEBM10UP	0.5	M 10 (x1.50)	10	17	20	6	30	34	60	57	0.24	10
4215SEBM12UP	0.8	M 12 (x1.75)	15	21	20	6	30	34	60	57	0.24	10
4215SEBM16UP	1.4	M 16 (x2)	50	27	35	8	38	45	88	80	0.8	10
4215SEBM20UP	2	M 20 (x2.5)	100	30	35	8	38	45	88	80	0.8	10
4215SEBM243T8UP	3.2	M 24 (x3)	160	36	35	14	38	45	88	80	0.8	10
4215SEBM244T2UP	3.4	M 24 (x3)	160	36	50	14	58	70	115	106	2.6	10
4215SEBM30UP	5.5	M 30 (x3.5)	250	45	50	14	58	70	115	106	2.7	10
4215SEBM36UP	9	M 36 (x4)	320	54	70	14	83	94	168	155	7	10
4215SEBM42UP	12	M 42 (x4,5)	400	63	70	14	83	94	168	155	7	10
4215SEBM48UP	15	M 48 (x5)	600	68	70	19	80	94	168	155	7	10

Blueprint

