

Swivel Eye Bolt Codipro SEB UP

Product information



The SEB lifting ring is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load
- Safe alternative to C15 DIN 580 eye bolts.
- Torque key adaptor available on request.

Grade: GRADEUP (8+)

Material: High tensile steel

Marking: According to standard, CE-marked

Standard: EN 1677-1

except grade/WLL

Note: On request the product can be certified for lashing.

Safety factor: 5:1

| Part Code | WLL ton | Thread | Torque Nm | Standard L1 mm | X/X mm | S mm | A mm | B mm | C mm | D mm | Weight kg | Total price |
|----------------------|---------|--------------|-----------|----------------|--------|------|------|------|------|------|-----------|-------------|
| 11.42SEB M 8 UP | 0.4 | M 8 (x1.25) | 6 | 14 | 20 | 6 | 30 | 34 | 60 | 57 | 0.24 | N/A |
| 11.42SEB M 10 UP | 0.5 | M 10 (x1.50) | 10 | 17 | 20 | 6 | 30 | 34 | 60 | 57 | 0.24 | N/A |
| 11.42SEB M 12 UP | 0.8 | M 12 (x1.75) | 15 | 21 | 20 | 6 | 30 | 34 | 60 | 57 | 0.24 | N/A |
| 11.42SEB M 16 UP | 1.4 | M 16 (x2) | 50 | 27 | 35 | 8 | 38 | 45 | 88 | 80 | 0.8 | N/A |
| 11.42SEB M 20 UP | 2 | M 20 (x2.5) | 100 | 30 | 35 | 8 | 38 | 45 | 88 | 80 | 0.8 | N/A |
| 11.42SEB M 24 3T8 UP | 3.2 | M 24 (x3) | 160 | 36 | 35 | 14 | 38 | 45 | 88 | 80 | 0.8 | N/A |
| 11.42SEB M 24 4T2 UP | 3.4 | M 24 (x3) | 160 | 36 | 50 | 14 | 58 | 70 | 115 | 106 | 2.6 | N/A |
| 11.42SEB M 30 UP | 5.5 | M 30 (x3.5) | 250 | 45 | 50 | 14 | 58 | 70 | 115 | 106 | 2.7 | N/A |
| 11.42SEB M 36 UP | 9 | M 36 (x4) | 320 | 54 | 70 | 14 | 83 | 94 | 168 | 155 | 7 | N/A |
| 11.42SEB M 42 UP | 12 | M 42 (x4,5) | 400 | 63 | 70 | 14 | 83 | 94 | 168 | 155 | 7 | N/A |
| 11.42SEB M 48 UP | 15 | M 48 (x5) | 600 | 68 | 70 | 19 | 80 | 94 | 168 | 155 | 7 | N/A |

Blueprint

