



Double Swivel Ring Codipro SS DSR

Product information



Stainless Steel Double Swivel Ring: SS DSR.
Double articulation allows it to line up perfectly with the sling.
From M8 to M30 as standard; for loads from 0.3 t to 3 t.

Features:

- Rotatable under load.
- Two ways of tightening:- Allen key or Torque wrench(also for external hex)

Material: AISI 316 L

Marking: According to standard, CE-marked

Temperature range: -20°C up to + 200°C

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

Part Code	WLL ton	Thread	Torque Nm	StandardL1 mm	S1 mm	S2 mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg	Delivery time
4215SSDSRM6	0.1	M 6 (x1)	4	13	8	16	32	30	30	39	28	13	53	9,5	0.3	10
4215SSDSRM8	0.3	M 8 (x1.25)	6	16	8	16	32	30	30	39	28	13	53	9,5	0.3	10
4215SSDSRM10	0.5	M 10 (x1.50)	10	16	8	16	32	30	30	39	28	13	53	9,5	0.3	10
4215SSDSRM12	0.8	M 12 (x1.75)	15	19	8	16	32	30	30	39	28	13	53	9,5	0.3	10
4215SSDSRM14	1	M 14 (x2)	30	29	8	20	44	40	45	53	38	17	76	13	0.9	10
4215SSDSRM16	1.4	M 16 (x2)	50	26	8	20	44	40	45	53	38	17	76	13	0.9	10
4215SSDSRM18	1.4	M 18 (x2.5)	70	30	8	20	44	40	45	53	38	17	76	13	1	10
4215SSDSRM20	1.4	M 20 (x2.5)	100	30	8	20	44	40	45	53	38	17	76	13	1	10
4215SSDSRM22	2.2	M 22 (x2.5)	120	42	14	24	62	55	58	83	56	25	115	19	2.5	10
4215SSDSRM24	2.7	M 24 (x3)	160	42	14	24	62	55	58	83	56	25	115	19	2.6	10
4215SSDSRM27	2.8	M 27 (x3)	200	42	14	24	62	55	58	83	56	25	115	19	2.7	10
4215SSDSRM30	3	M 30 (x3,5)	250	47	14	24	62	55	58	83	56	25	115	19	2.8	10

Blueprint

