



Double Swivel Ring Codipro SS DSR

Product information



Stainless Steel Double Swivel Ring: SS DSR.
Double articulation allows it to line up perfectly with the sling.
From M8 to M30 as standard; for loads from 0.3 t to 3 t.

Features:

- Rotatable under load.
- Two ways of tightening:- Allen key or Torque wrench(also for external hex)

Material: AISI 316 L

Marking: According to standard, CE-marked

Temperature range: -20°C up to + 200°C

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

| Part Code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | L1 mm | S1 mm | S2 mm | Weight kg | Delivery time |
|--------------|---------|--------------|-----------|------|------|------|------|------|------|------|------|-------|-------|-------|-----------|---------------|
| 4215SSDSRM6 | 0.1 | M 6 (x1) | 4 | 32 | 30 | 30 | 39 | 28 | 13 | 53 | 9.5 | 15 | 8 | 16 | 0.3 | 10 |
| 4215SSDSRM8 | 0.3 | M 8 (x1.25) | 6 | 32 | 30 | 30 | 39 | 28 | 13 | 53 | 9.5 | 16 | 8 | 16 | 0.3 | 10 |
| 4215SSDSRM10 | 0.5 | M 10 (x1.50) | 10 | 32 | 30 | 30 | 39 | 28 | 13 | 53 | 9.5 | 16 | 8 | 16 | 0.3 | 10 |
| 4215SSDSRM12 | 0.8 | M 12 (x1.75) | 15 | 32 | 30 | 30 | 39 | 28 | 13 | 53 | 9.5 | 19 | 8 | 16 | 0.3 | 10 |
| 4215SSDSRM14 | 1 | M 14 (x2) | 30 | 44 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 29 | 8 | 20 | 0.9 | 10 |
| 4215SSDSRM16 | 1.4 | M 16 (x2) | 50 | 44 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 26 | 8 | 20 | 0.9 | 10 |
| 4215SSDSRM18 | 1.4 | M 18 (x2.5) | 70 | 44 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 30 | 8 | 20 | 1 | 10 |
| 4215SSDSRM20 | 1.4 | M 20 (x2.5) | 100 | 44 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 30 | 8 | 20 | 1 | 10 |
| 4215SSDSRM22 | 2.2 | M 22 (x2.5) | 120 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 42 | 14 | 24 | 2.5 | 10 |
| 4215SSDSRM24 | 2.7 | M 24 (x3) | 160 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 42 | 14 | 24 | 2.6 | 10 |
| 4215SSDSRM27 | 2.8 | M 27 (x3) | 200 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 42 | 14 | 24 | 2.7 | 10 |
| 4215SSDSRM30 | 3 | M 30 (x3,5) | 250 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 47 | 14 | 24 | 2.8 | 10 |

Blueprint

