

Double Swivel Shackle Codipro SS DSS

Product information



The SS.DSS stainless steel lifting ring is a double swivel ring. It is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Stainless steel ring that provides maximum corrosion resistance.
- Rotatable under load.
- M45 to M56 or UNC thread available on request.

... [Read more](#)

Material: AISI 316 L

Marking: According to standard, CE-marked


Temperature range: -20°C up to + 200°C

Standard: EN 1677-1
except grade/WLL

Safety factor: 5:1

Double Swivel Shackle Codipro SS DSS

Blueprint



Lifting table

| Part code | WLL ton | Thread | Torque Nm | Standard L1 mm | A mm | B mm | C mm | D mm | E mm | F mm | G, mm | L1mm mm | S mm | Weight kg |
|----------------|---------|-------------|-----------|----------------|------|------|------|------|------|------|-------|---------|------|-----------|
| 4215SSDSSM24 | 2.7 | M 24 (x3) | 160 | 36 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 36 | 19 | 5.2 |
| 4215SSDSSM30 | 3.5 | M 30 (x3,5) | 250 | 45 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 45 | 19 | 5.2 |
| 4215SSDSSM33 | 3.5 | M 33 (x3,5) | 250 | 50 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 50 | 19 | 5.2 |
| 4215SSDSSM36 | 5 | M 36 (x4) | 320 | 54 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 54 | 19 | 5.2 |
| 4215SSDSSM36x3 | 5 | M 36 (x3) | 320 | 54 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 54 | 19 | 5.2 |
| 4215SSDSSM39 | 5 | M 39 (x4) | 320 | 54 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 54 | 19 | 5.4 |
| 4215SSDSSM42 | 6 | M 42 (x4,5) | 400 | 63 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 63 | 19 | 5.4 |
| 4215SSDSSM42x3 | 6 | M 42 (x3) | 400 | 63 | 61 | 31 | 70 | 98 | 73 | 149 | 30 | 63 | 19 | 5.4 |