



Beam Clamp IPTKU

Product information



General:

The IPTKU series beam clamp has an improved hinged hoisting eye that increases the loading angles and an optional new "Double Locking Device"

Features:

- Available in capacities of 2 thru 10 metric tons.
- Wide variety of jaw openings available: 75 to 460 mm".
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.

Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

| Part code | WLL ton | Jaw width mm | Model | Jaw A | C mm | D mm | E mm | H mm | J mm | K mm | Weight kg | Delivery time |
|-----------------|---------|--------------|----------|---------|---------|------|------|------|------|------|-----------|---------------|
| 502300201900020 | 2 | 75-190 | 2-IPTKU | 75-190 | A + 100 | 121 | 76 | 22 | 99 | 19 | 5.7 | 10 |
| 502300301900020 | 3 | 75-190 | 3-IPTKU | 75-190 | A + 100 | 121 | 89 | 22 | 122 | 22 | 6.4 | 10 |
| 502300402800020 | 4 | 120-180 | 4-IPTKU | 120-180 | A + 150 | 140 | 89 | 40 | 122 | 22 | 12.1 | 10 |
| 502300503500020 | 5 | 120-350 | 5-IPTKU | 120-350 | A + 175 | 140 | 89 | 40 | 122 | 22 | 14.5 | 10 |
| 502301004600020 | 10 | 200-460 | 10-IPTKU | 200-460 | A + 300 | 200 | 105 | 60 | 152 | 26 | 41 | 10 |

Blueprint

