Beam Clamp IPTKU

Product information



The Crosby IPTKU series beam clamp has an improved hinged hoisting eye that increases the loading angles and WLL range from 2 to 10 tonnes.

Best used for:

- Transferring steel beams in industrial lifting and material handling operations.
- Applications requiring specific hoisting eye configurations and jaw openings matched to the load.

Product benefits:

- Welded alloy steel body provides strength with compact dimensions.
- Jaw openings from 75 to 460 mm accommodate different beam dimensions.
- Individually proof tested to twice the WLL, with certification supplied.
- Permanent WLL identification and individual serial numbers support inspection and traceability.
- Supplied with documentation; available maintenance and repair kits support servicing.

... *Read more*


Material: Alloy steel.
Marking: According to standard, CE-mark, WLL, Logo, Type, Jaw opening, Serial number, Proof load test date
Temperature range: -40°C (-40°F) up to +100°C (+212°F)
Standard: EN 13155

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Beam Clamp IPTKU

Blueprint



Lifting table

Part code	WLL ton	Jaw width mm	Model	Jaw A mm	C mm	D mm	E mm	H mm	J mm	K mm	Weight kg
502300201900020	2	75-190	2-IPTKU	75-190	A + 100	121	76	22	99	19	5.7
502300301900020	3	75-190	3-IPTKU	75-190	A + 100	121	89	22	122	22	6.4
502300402800020	4	120-180	4-IPTKU	120-180	A + 150	140	89	40	122	22	12.1
502300503500020	5	120-350	5-IPTKU	120-350	A + 175	140	89	40	122	22	14.5
502301004600020	10	200-460	10-IPTKU	200-460	A + 300	200	105	60	152	26	41

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved