

Beam Clamp IPBC

Product information



General:

The IPBC horizontal lifting clamps have a pretension feature that allows the user to attach the clamps to the material for horizontal lifting and transfer of sagging and non-sagging material. These clamps may also be used to handle material that will be used in shears, bending and rolling machines or other fabrication equipment. May also be used for turning beams from the "H" into the "I" position. Thanks to the special construction with the ergonomic lever, your work is made light & easy and can be carried out by a single person.

Features:

- Available in capacities of 1 thru 4.5 metric tons.
- Jaw openings available: 0 to 40mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

[... Read more](#)

Features:


Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Beam Clamp IPBC

Blueprint



Lifting table

Part code	Code	WLL ton	Jaw width mm	A mm	B mm	C mm	E mm	F mm	G, mm	H, mm	J mm	K mm	L mm	Weight kg
502100100200210	1-IPBC	1	0-20	0-20	132	52	26	75	185	36	16	182	12	3.5
502100200250210	2-IPBC	2	0-25	0-25	152	62	30	82	210	49	20	218	15	6.5
502100300250210	3-IPBC	3	0-25	0-25	157	66	30	82	210	57	20	225	15	8.5