# Swivel Jaw / Jaw Crosby S2

## Product information

**Design:** Swivel with jaws equipped with tapered roller thrust bearing.

**Features:**

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

... *Read more*

**Marking:** CE-marked
**Note:** Always check before use if your steel wire rope is suitable for use with a swivel.
**Warning:** Not to be used on demolition- (wrecking-) balls!

**Safety factor:** 5:1

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© September 2026 - All Rights Reserved

# Swivel Jaw / Jaw Crosby S2

## Blueprint




## Lifting table

| Part code | Rope Ø range mm | WLL ton | Swivel No | B mm | G mm | H mm | J mm | K mm | N mm | O mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 422500300080 | 13 | 3 | 3-S-2 | 236 | 70 | 19.1 | 22.4 | 41.1 | 33.3 | 25.4 | 4.37 |
| 422500500080 | 16 | 5 | 5-S-2 | 262 | 76 | 22.4 | 25.4 | 57 | 41.1 | 28.4 | 6.21 |
| 422500850080 | 19 | 8.5 | 8-S-2 | 321 | 102 | 25.4 | 39.5 | 71.5 | 54 | 35.1 | 11.9 |
| 422501000080 | 22 | 10 | 10-S-2 | 426 | 114 | 38.1 | 44.5 | 86 | 89 | 44.5 | 20.8 |
| 422501500080 | 26 | 15 | 15-S-2 | 435 | 127 | 38.1 | 44.5 | 86 | 89 | 44.5 | 28.5 |
| 422502500080 | | 25 | 25-S-2 | 527 | 152 | 51 | 51 | 117 | 93.5 | 60.5 | 64 |
| 422503500080 | | 35 | 35-S-2 | 527 | 165 | 51 | 51 | 117 | 93.5 | 60.5 | 70 |
| 422504500080 | | 45 | 45-S-2 | 641 | 178 | 57 | 63.5 | 127 | 102 | 76 | 107 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© September 2026 - All Rights Reserved