Shackle Crosby G-2160, Wide Body

Product information



The Crosby G-2160 wide body shackle is designed for heavy-duty lifting applications using wire rope, synthetic web and round slings. Its wide bow distributes the load over a larger contact area, increasing usable sling strength by at least 15% and helping extend wire rope sling service life. Available with working load limits (WLL) from 7 to 2,000 metric tonnes.

Best used for:

- Heavy lifting operations requiring high-capacity connections and improved sling load distribution.
- Lifting assemblies using wire rope or synthetic slings, including inline bow-to-bow connections.

Product benefits:

- Wide body design increases usable sling strength by at least 15%.
- Quenched and tempered construction provides strength for demanding lifting applications.
- Individual proof testing and magnetic particle inspection support documented quality verification.
- DNV type approval and certification support compliance documentation for lifting operations.
- Hot-dip galvanized or Dimetcoted finish, depending on size, provides corrosion protection.

... *Read more*

Material: Forged alloy steel from 7 through 300 metric tons. Cast alloy steel from 400 through 1550 metric tons.
Marking: According to standard, CE-mark, WLL. Shackles, 30t and larger, are RFID EQUIPPED.
Temperature range: -40° C un to +204° C
Finish: 7-55 tons are galvanized with painted pin. 75t and larger, bows are furnished Dimetcoted, and pins are Dimetcoted, then painted.
Standard: DNV-OS-E101, DNV-ST-0377, DNV-ST-0378


Safety factor: 7-300 t 5:1 ; 400 t < 4,5:1.

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Shackle Crosby G-2160, Wide Body

Blueprint



Lifting table

Part code	WLL ton	Effective body Ø mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	M mm	N mm	P mm	R mm	Weight kg
420100700260	7	53	32	22	90	41	64	46	104	149	32	32	-	105	-	24	18	1.81
420101250260	12.5	61	43	29	118	54	83	61	140	194	35	41	-	137	-	32	23	3.99
420101800260	18	71	52	35	148	64	102	68	172	238	38	51	-	170	-	36	30	6.76
420103000260	30	104	70	41	176	80	127	89	216	289	64	64	-	206	-	45	35	11.9
420104000260	40	91	86	51	205	95	152	102	270	346	44	76	-	259	-	59	43	21.2
420105500260	55	109	83	57	238	114	178	118	311	397	51	89	-	263	-	67	51	30.8
420107500260	75	160	105	70	293	127	185	136	321	474	95	93	102	382	46	70	61	50.8
420112500260	125	173	130	80	365	150	220	165	393	584	95	110	102	465	46	89	79	87.5
420120000260	200	241	150	105	480	217	275	214	515	773	133	138	102	491	46	126	86	191
420130000260	300	290	187	133	600	264	321	267	608	957	156	160	102	574	46	147	109	365
420140000260	400	363	220	160	620	360	375	314	668	1,062	183	188	-	780	-	205	150	535
420150000260	500	439	250	180	685	435	455	340	792	1,190	222	228	-	863	-	245	164	796
420160000260	600	480	276	200	740	475	489	375	816	1,292	243	263	-	938	-	265	182	1,002
420180000260	800	540	342	230	820	536	554	440	904	1,462	272	300	-	1,078	-	307	212	1,535
420110000261	1,000	643	404	270	850	610	640	500	1,116	1,584	338	320	-	1,187	-	349	233	2,263
420112500261	1,250	709	442	300	928	675	708	570	1,259	1,749	371	354	-	1,322	-	386	249	3,085
420115500261	1,550	757	470	320	1,010	720	755	615	1,314	1,891	397	379	-	1,427	-	413	290	3,802

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved