Steel wire rope Diepa H43 (SKZ8 P)

Product information



Diepa H43 is a wire rope with compacted inner and outer strands and plastic insert. The rope has a very high breaking force.

Applications: For all different types of cranes where rotation resistant steel wire rope is not required. Lifting wire for mobile cranes, deck cranes and container cranes where multiple parts is being used in lower lifting operations, and where right -and left hand lays are being used in at the same time. Winch and digging machines

Lay: Ordinary lay with internal plastic component.

Total number of wires: 4-6 mm 95, 7-15 mm 262, 16-24 mm 319, 25-44 mm 347, 45-64 mm 427, 65-76 mm 487
ISO 4309 Rope Category No: 4-6 mm **RCN.02**, 7-15 mm **RCN.04**, 16-44 mm **RCN.09**, 45-76 mm **RCN.13**

... *Read more*

Marking: According to standard
Finish: Galvanized or bright.
Standard: EN 12385-4
Warning: Not to be used with a swivel.

Fill factor: 0.7403
RCN: 02

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Steel wire rope Diepa H43 (SKZ8 P)

Lifting table

Part code	Rope diameter	Tensile strength N/mm²	Finish	Rope lay
103101404900209	14	2,160	Others_Special	sZ

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved