# Solid Thimble Selfcolored

**Product information**



Solid Thimbles DIN 3091 are forged wire rope thimbles designed to protect rope eyes from wear, deformation, and concentrated loading at connection points. They are used in lifting, rigging, marine, and industrial wire rope assemblies where maintaining the shape and service life of the rope termination is important. Manufactured in accordance with DIN 3091 and EN 13411-9 dimensional requirements.

**Best used for:**

- Wire rope eye terminations in lifting, rigging, and load-handling applications.
- Installations requiring durable rope protection and consistent eye geometry under load.

**Product benefits:**

- Solid forged construction helps resist deformation under service loads.
- Protects wire rope eyes from abrasion and concentrated wear.
- DIN 3091 dimensions support compatibility with standard rope assemblies.
- Available for wire rope diameters from 8 mm to 72 mm.
- Standard hole sizes with optional drilling and bronze bushing modifications

... *Read more*


**Marking:** According to standard
**Standard:** EN 13411-9

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# Solid Thimble Selfcolored

## Blueprint




## Lifting table

| Part code | Rope Ø range mm | Standard hole D1 mm | Possible drilled hole D1 mm | C mm | RW mm | l mm | Weight kg/100pc |
|---|---|---|---|---|---|---|---|
| 123100800640 | 8 | 14 | 17-20 | 40 | 9 | 56 | 18.1 |
| 123101000640 | 10 | 18 | 21-25 | 50 | 11 | 70 | 31.8 |
| 123101200640 | 12 | 21 | 24-30 | 60 | 13 | 84 | 51.5 |
| 123101400640 | 14 | 25 | 29-35 | 70 | 16 | 98 | 79.9 |
| 123101600640 | 16 | 28 | 32-40 | 80 | 18 | 130 | 89.5 |
| 123101800640 | 18 | 31 | 35-45 | 90 | 20 | 145 | 121.1 |
| 123102000640 | 20 | 35 | 40-50 | 100 | 22 | 161 | 161 |
| 123102200640 | 22 | 38 | 43-55 | 110 | 24 | 177 | 211 |
| 123102400640 | 24 | 41 | 46-60 | 120 | 26 | 193 | 271 |
| 123102600640 | 26 | 44 | 49-65 | 130 | 29 | 209 | 355 |
| 123102800640 | 28 | 47 | 52-70 | 140 | 31 | 224 | 420 |
| 123103200640 | 32 | 53 | 58-80 | 160 | 35 | 256 | 630 |
| 123103600640 | 36 | 59 | 65-90 | 180 | 40 | 288 | 884 |
| 123104000640 | 40 | 65 | 71-100 | 200 | 44 | 320 | 1,100 |
| 123104400640 | 44 | 70 | 76-110 | 220 | 48 | 352 | 1,500 |
| 123104800640 | 48 | 76 | 82-120 | 240 | 53 | 384 | 2,000 |
| 123105200640 | 52 | 81 | 87-130 | 260 | 57 | 416 | 2,500 |
| 123105600640 | 56 | 86 | 92-140 | 280 | 62 | 448 | 3,200 |
| 123106400640 | 64 | 95 | 103-160 | 320 | 70 | 512 | 4,600 |
| 123107200640 | 72 | 140 | 145-180 | 360 | 79 | 576 | 6,600 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved