Shackle Gunnebo SMS 1577C

Product information



Shackle 1577 C is a Class 3 straight shackle with a threaded pin for rigging connections. Available variants have rated loads from 0.6 to 2.4 tonnes and a 5:1 safety factor. Select the correct size and do not exceed its rated load.

Best used for:

- Rigging connections requiring a Class 3 straight shackle.
- Assemblies where the rated load and pin dimensions match the connected hardware.

Product benefits:

- Thread sizes from M10 to M20 provide options across the listed load ratings.
- Hot-dip galvanizing gives the steel shackle a protective surface finish.
- A ±5% forging tolerance on internal dimensions helps manage fit.

... *Read more*

Marking: CE-mark, WLL, code and grade.
Finish: Hot-dip galvanized


Safety factor: 5:1
Grade: 3

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Shackle Gunnebo SMS 1577C

Blueprint



Lifting table

Part code	WLL ton	Thread mm	A mm	C mm	D mm	D1 mm	D2 mm	c* mm	Weight kg
420100060440	0.6	M10	15	30	8.5	M10	20	30	0.1
420100090440	0.9	M12	20	39	11	M12	26	39	0.2
420100150440	1.5	M16	24	52	13	M16	33	52	0.4
420100240440	2.4	M20	28	65	16	M20	42	65	0.65

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved