

Black Theater Round Sling

Product information



Typically used in connection with theaters, scenes etc. where the round sling preferably should not be visible.

Design: Load carrying yarn covered with "seamless" black protection sleeve.

Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL) $\pm 2\%$.

[... Read more](#)

Material: Polyester. Resistant to most acids but not to strong alkalizes.


Marking: According to standard, Manufacture ID, WLL, length, date.

Temperature range: Approx. -40° up to $+100^{\circ}\text{C}$.

Standard: EN 1492-2

Black Theater Round Sling

Blueprint



Lifting table

Part code	EWL m	WLL ton	WLL Straight Lift ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Colour
340100110050270	0.5	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100110100270	1	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100110150270	1.5	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100110200270	2	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100110300270	3	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100110400270	4	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100110700270	7	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100111000270	10	1.1	1.1	0.9	2.2	1.5	1.1	Black
340100210050270	0.5	2.1	2.1	1.7	4.2	2.9	2.1	Black
340100210100270	1	2.1	2.1	1.7	4.2	2.9	2.1	Black
340100210150270	1.5	2.1	2.1	1.7	4.2	2.9	2.1	Black
340100210200270	2	2.1	2.1	1.7	4.2	2.9	2.1	Black
340100210250270	2.5	2.1	2.1	1.7	4.2	2.9	2.1	Black
340100210300270	3	2.1	2.1	1.7	4.2	2.9	2.1	Black
340100210400270	4	2.1	2.1	1.7	4.2	2.9	2.1	Black