



## Manual Chain Hoist KITO CB Series

### Product information

# KITO

The KITO CB Series chain hoists have a shock resistant gear casing, double ratcheted spring, precision gears and double casing (to protect against dust and water), mechanical breaks, load chain guide and long-life chain. Reliable, durable and easy to use. Capacity from 500 kg to 50 t (special design up to 100 t).

#### Options:

- Plain trolley
- Geared trolley
- Canvas chain bucket
- Overload limiter

**Material:** Nickel plated load chain, grade 10.

**Marking:** Type plate with WLL, CE-marking and serial number.

**Finish:** Painted.

**Safety factor:** 4:1.

Part Code	Code	WLL ton	Lifting height m	s mm	Load chain Ø mm	Chain falls	Chain pull to lift full load in daN	A mm	B mm	C mm	e mm	f mm	g mm	t mm	Weight kg	Total price
16.10CB005SSH030030	CB005	0.5	3	35,5	5,0 x 15,1	1	23,5	158	161	285	69	99	27	12,1	-	N/A
16.10CB010SSH030030	CB010	1	3	42,5	6,3 x 19,1	1	28,4	162	161	295	71	99	29	16,0	11.5	N/A
16.10CB015SSH030030	CB015	1.5	3	47,5	7,1 x 21,2	1	34,3	171	182	350	78	112	34	19,5	14.5	N/A
16.10CB020SSH030030	CB020	2	3	50,0	8,0 x 24,2	1	35,3	182	202	375	87	125	36	21,8	20	N/A
16.10CB025SSH030030	CB025	2.5	3	53,0	9,0 x 27,2	1	32,3	192	233	420	91	143	40	24,3	27	N/A
16.10CB030SSH030030	CB030	3	3	56,0	7,1 x 21,2	2	35,3	171	235	510	78	162	42,5	27,2	24	N/A
16.10CB050SSH030035	CB050	5	3	63,0	9,0 x 27,2	2	33,3	192	282	600	91	194	46,5	34,5	41	N/A
16.10CB075SSH035040	CB075	7.5	3.5	85,0	9,0 x 27,2	3	34,3	192	373	770	91	253	72,5	47,5	63	N/A
16.10CB100SSH035050	CB100	10	3.5	85,0	9,0 x 27,2	4	35,3	192	438	760	111	308	72,5	47,5	83	N/A
16.10CB150SSH035045	CB150	15	3.5	100	9,0 x 27,2	6	36,3	268	492	1,020	119	337	80,0	60,0	155	N/A
16.10CB200SSH035045	CB200	20	3.5	110	9,0 x 27,2	8	35,3 x 2	374	746	1,180	187	373	81,0	67,0	235	N/A
16.10CB300SSH035045	CB300	30	35	125	9,0 x 27,2	10	42,1 x 2	404	746	1,300	202	373	103	85,0	310	N/A
16.10CB400SSH035045	CB400	40	3.5	140	9,0 x 27,2	14	42,1 x 2	502	760	1,480	251	380	104	95,0	480	N/A
16.10CB500SSH035045	CB500	50	3.5	155	9,0 x 27,2	16	48,0 x 2	544	796	1,560	272	398	112	106,0	640	N/A

# Blueprint

