



Electric Chain Hoist KITO ED Series

Product information

General: The KITO ED electric chain hoist is compact, light-weight, reliable and weather- and corrosion-resistant. It has an aluminum gearbox, high performance mechanical brake, adjustable speed built-in potentiometer and a maximal speed of 20,1 m/min. The hook suspension type is offered with single or dual lifting speed. The cylinder control type (EDC) is offered with dual lifting speed.

Options:

- Plain trolley
- Geared trolley
- Canvas chain bucket up to 70 m
- Steel chain bucket
- Radio remote control

Marking: According to standard, Type plate with WLL, CE-marking and serial number.

Temperature range: -20°C up to 40°C

Finish: Nickel plated load chain grade 80 (DAT) in accordance with EN 818-7.

Standard: EN 818-7

Code	WLL	Lifting height m	Model	Headroom mm	Chain falls	Class FEM	Lifting speed m/min.	Duty rating % ED	Weight	Delivery time
ED06S	0.06	3	ED single speed	315	1	1Am	20.1	30	11.5	10
ED06ST	0.06	3	ED dual speed	315	1	1Am	20.1/4.0	30	12	10
EDC06SD	0.06	1.8	EDC dual speed	945	1	1Am	20.1/4.0	30	14.5	10
ED10S	0.1	3	ED single speed	315	1	1Am	12.5	30	11.5	10
ED10ST	0.1	3	ED dual speed	315	1	1Am	12.5/3.0	30	12	10
EDC10SD	0.1	1.8	EDC dual speed	945	1	1Am	12.5/3.0	30	14.5	10
EDC16SD	0.16	1.8	EDC dual speed	960	1	1Am	19.2/4.0	30	11.5	10
ED16S	0.16	3	ED single speed	330	1	1Am	19.2	30	15.5	10
ED16ST	0.16	3	ED dual speed	330	1	1Am	19.2/4.0	30	16	10
ED18S	0.18	3	ED single speed	315	1	1Am	7.7	20	11.5	10
ED18ST	0.18	3	ED dual speed	315	1	1Am	7.7/3.0	20	12	10
EDC18SD	0.18	1.8	EDC dual speed	945	1	1Am	7.7/3.0	20	14.5	10
ED24S	0.24	3	ED single speed	330	1	1Am	12.9	30	15.5	10
ED24ST	0.24	3	ED dual speed	330	1	1Am	12.9/3.0	30	16	10
EDC24SD	0.24	1.8	EDC dual speed	960	1	1Am	12.9/3.0	30	18.5	10
ED48ST	0.48	3	ED dual speed	520	2	1Am	6.4/2.0	30	21	10
ED48S	0.48	3	ED single speed	520	2	1Am	6.4	30	21	10