

Roundsling Polyester – Heavy-Lift

Product information



LIFT-TEX®

HEAVY LIFT SLINGS



High quality product with very small length tolerances produced in Europe. Produced in capacities (WLL) up to 300 tons. Available with different types of protection.

Chemical resistance: Resistant to most acids, but not strong alkalizes.

Certificate: CE-Declaration. DNV/Lloyd's Proofload certificates on demand.

Characteristics:

- High life cycle if correctly used (with proper protections).
- Very flexible, cost saving and easy to handle.
- Excellent technical performance.
- High lifting capacity. (Be aware of big diameters in polyester in combination with shackles/hooks).
- Different sling configurations (on demand).
- Small length tolerances.
- More options for RFID.
- Extra protection on demand. The use of (extra) appropriate protections is always recommended on the bearing points.
- Different protections for sharp edges, corners, etc. (PES, PU, PVC, HMPE).

Material: 100% High Tenacity Polyester core and cover.

Marking: According to standard, CE-marked, manufacturer's symbol, working load limit (WLL), length, and a label with handling instruction.

Temperature range: -40°C – +100°C

Standard: EN 1492-2

Note: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Part Code	WLL ton
340100100300141	1
340100200200141	2
340100300200140	3
340100400400140	4
340100500000140	5
340100600600140	6
340100800000140	8
340101001000140	10
340101200000141	12
340101500800140	15
340102001000140	20
340102500400140	25
340103000000140	30
340103500800140	35
340104000000141	40
340105000000140	50
340106000000141	60
340107000000141	70
340108000000141	80
340108500000141	85
340109000000141	90
340110000000141	100

340112000000140	120
340112500000141	125
340115000000141	150
340117500000141	175
340118000000141	180
340120000000141	200

Technical data